

## Options and Accessories



Turn Signals



Locking Glove Box



Heavy-Duty Bumper/  
West Coast Mirror



Wheel Covers



Fold-Down  
Windshield



Battery Capacity  
Indicator



Canopy Top  
White



Fuel Gauge  
and Hour Meter



Custom Van Box



Stake-Side Kit



Certified ROPS  
Cab Enclosure



Trailer Hitch



Pintle Hitch



Cab Heater



Safety Strobe Light



Toolbox

### Value Packages

	Heavy-Duty Bumper	Trailer Hitch	Hour Meter*	Differential Guard	Radio/Beverage Holder	Cargo Box**	Extra-Traction Rear Tires	8.5-Inch Premium Tread Front Tires
<b>Carryall 1 Electric</b>	✓	✓	✓	✓	✓	Standard	✓	Standard
<b>Carryall 1 Gasoline</b>	✓	✓	Standard	✓	✓	Standard	✓	Standard

\*Fuel Gauge/Hour Meter is standard on all gas vehicles listed.  
\*\*Priced separately from base vehicle.



Ingersoll Rand is a world leader in the field of compact vehicles and equipment. Our widely known Bobcat® brand includes an extensive line of powerful, nimble compact construction equipment and attachments, and our state-of-the-art engineering capabilities and stylish designs are reflected in our world famous Club Car® vehicles.

1.800.ClubCar • +1 706.863.3000

www.clubcar.com www.bobcat.com www.ingersollrand.com

Club Car

# CARRYALL 1

## UTILITY VEHICLE



# CARRYALL

# 1

From airports to colleges to zoos, the Carryall 1 is the perfect utility vehicle for light-duty jobs. The Carryall 1 is powered by your choice of a 351 cc, 11.5 hp gas engine or Club Car's IQ System™ electric motor. With the standard IQ System, the



Carryall 1 electric model features programmable speed control, consistent hill climbing and the overall performance that makes it feel more like a gas model. And Club Car's exclusive aluminum frame is up to three times stronger than comparable steel frames.



## Features

Club Car's exclusive IQ System electric or 11.5 hp gas engine



9.1 ft<sup>3</sup> (0.3 m<sup>3</sup>) cargo box carries 300 lb (136.1 kg)



Rugged, rustproof aluminum frame, chassis and cargo box



Self-adjusting rack & pinion steering




ArmorFlex® front body for fade-resistant color



Standard Color: Dark Gray



Optional Colors: Beige Gray, Green, White, Classic Blue, Red, Black and Burgundy



4-ply, premium tread tires



Smooth, independent front and semi-independent rear suspension

## Additional Features

- **Maximum speed of 19 mph (30.6 kph)** (Electric vehicles only)
- **Side fuel fill**
- **800 lb (363.2 kg) total vehicle capacity**
- **48-volt IQ System electric motor or 351 cc, 11.5 hp gas, pedal-start engine**
- **Maximum hp @ 3,600 rpm exceeds SAE J1940 Performance Standards**
- **Reconfigured dash**
- **Redesigned hip restraint for maximum styling and comfort**

## Specifications

	<i>Carryall 1 Electric</i> <small>with exclusive IQ System</small>	<i>Carryall 1 Gasoline</i>	
<b>POWER SUPPLY</b>	<b>Engine</b>	N/A	Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
	<b>Drive Motor</b>	48-volt Shunt/Sepex	N/A
	<b>Horsepower</b>	3.2 @ 2400 rpm (continuous) 10.0 @ 1125 RPM (intermittent)	11.5**
	<b>Governor</b>	N/A	Automatic ground speed sensing, internally geared-in unitized transaxle
	<b>Governed RPM</b>	N/A	3050±30
	<b>Ignition</b>	N/A	Electronic w/electronic RPM limiter
	<b>Drive Unit</b>	12.3:1 direct-drive axle, double-reduction helical gear	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
	<b>Electrical System</b>	48-volt	12-volt, 500 cca 105 min. reserve
	<b>Batteries</b>	Six 8-volt 117 min. @ 56 amp	N/A
	<b>Charger</b>	Automatic 48-volt DC, 17 amp, UL and CUL listed	N/A
<b>Controller</b>	300 amp Solid State	N/A	
<b>STEERING/ SUSPENSION</b>	<b>Steering</b>	Self-adjusting rack & pinion	Self-adjusting rack & pinion
	<b>Front Suspension</b>	Independent leaf spring w/dual hydraulic shocks	Independent leaf spring w/dual hydraulic shocks
	<b>Rear Suspension</b>	Leaf springs w/dual hydraulic shocks	Leaf springs w/dual hydraulic shocks
	<b>Brakes</b>	Self-adjusting rear-wheel mechanical drum	Self-adjusting rear-wheel mechanical drum
	<b>Park Brake</b>	Foot-operated, multi-lock	Foot-operated, multi-lock
	<b>Stabilizer Bar</b>	No	Yes
<b>FRAME/CHASSIS</b>	<b>Frame/Chassis</b>	Aluminum I-Beam	Aluminum I-Beam
	<b>Front Body</b>	ArmorFlex®	ArmorFlex®
	<b>Rear Body</b>	All aluminum	All aluminum
	<b>Body Finish</b>	Matching paint over molded-in color	Matching paint over molded-in color
	<b>Light Package</b>	Optional	Optional
	<b>Trailer Hitch</b>	Optional	Optional
	<b>Front Tires</b>	18 x 8.50-8, 4-ply rated, Premium tread	18 x 8.50-8, 4-ply rated, Premium tread
	<b>Rear Tires</b>	18 x 8.50-8, 4-ply rated, Premium tread	18 x 8.50-8, 4-ply rated, Premium tread
	<b>Instrumentation</b>	Battery warning light	Electronic fuel gauge/hour meter, low-oil warning light
<b>DIMENSIONS</b>	<b>Cargo Box Size</b>	37.6" x 45.1" x 9.3" (9.1 ft <sup>3</sup> ) 95.6 cm x 114.6 cm x 23.5 cm	37.6" x 45.1" x 9.3" (9.1 ft <sup>3</sup> ) 95.6 cm x 114.6 cm x 23.5 cm
	<b>Flat Bed Size</b>	35.8" x 44.3" (90.8 cm x 112.4 cm)	35.8" x 44.3" (90.8 cm x 112.4 cm)
	<b>Bed Height</b>	27.5" (69.9 cm)	27.5" (69.9 cm)
	<b>Bed Capacity</b>	300 lb. (136.1 kg)	300 lb. (136.1 kg)
	<b>Total Vehicle Capacity</b>	800 lb. (363.2 kg)	800 lb. (363.2 kg)
	<b>Overall Length</b>	103.5" (262.9 cm)	103.5" (262.9 cm)
	<b>Overall Width</b>	48.0" (121.9 cm)	48.0" (121.9 cm)
	<b>Overall Height</b>	48.0" (121.9 cm)	48.0" (121.9 cm)
	<b>Wheelbase</b>	65.5" (166.4 cm)	65.5" (166.4 cm)
	<b>Ground Clearance Under Differential</b>	4.5" (11.4 cm)	4.5" (11.4 cm)
	<b>Fuel Tank Capacity</b>	N/A	7.0 gallons (26.5 Liters)
	<b>Tread</b>	34.5"/38.5" (87.6 cm/97.8 cm)	34.5"/38.5" (87.6 cm/97.8 cm)
	<b>Dry Weight Less Batteries</b>	530 lb. (240.6 kg)	658 lb. (298.7 kg)
	<b>Speed Range</b>	8-19 mph (12.8-30.6 kph)	12-15 mph (19.3-24.1 kph)
	<b>Outside Clearance Circle</b>	17.5 ft. (5.3 m) dia.	17.5 ft. (5.3 m) dia.
	<b>Turning Radius</b>	8.4 ft. (2.6 m)	8.4 ft. (2.6 m)
<b>Intersecting Aisle Radius</b>	72.0" (182.9 cm)	72.0" (182.9 cm)	
<b>Vehicle Warranty</b>	2-year limited*	2-year limited	

\*4-year, limited battery warranty for electric vehicles  
\*\*Exceeds SAE J1940 Performance Standards