

Options and Accessories



Turn Signals



Locking Glove Box



Heavy-Duty Bumper/
West Coast Mirror



Wheel Covers



Heavy-Duty
Batteries



Battery Capacity
Indicator



Canopy Top
White



Fuel Gauge
and Hour Meter



Custom Van Box



Fold-Down
Windshield



Electric Bed Lift



Certified ROPS
Cab Enclosure



Safety Strobe Light



Toolbox



2-Inch Rear
Receiver Hitch



Pintle Hitch



Cab Heater



Swisher Dump Cart



50-Gallon Sprayer



Stake-Side Kit

Value Packages

	Heavy-Duty Bumper	Headlights	Trailer Hitch	Hour Meter*	Differential Guard	Radio/Beverage Holder	Cargo Box**	Extra-Traction Rear Tires	8.5-Inch Premium Tread Front Tires
Carryall 2 Electric	Standard	✓	Standard	✓	✓	✓	Standard	Standard	Standard
Carryall 2 Gasoline	Standard	✓	Standard	Standard	✓	✓	Standard	Standard	Standard

*Fuel Gauge/Hour Meter is standard on all gas vehicles listed.
**Priced separately from base vehicle.



Ingersoll Rand is a world leader in the field of compact vehicles and equipment. Our widely known Bobcat® brand includes an extensive line of powerful, nimble compact construction equipment and attachments, and our state-of-the-art engineering capabilities and stylish designs are reflected in our world famous Club Car® vehicles.

1.800.ClubCar • +1 706.863.3000

www.clubcar.com www.bobcat.com www.ingersollrand.com

Club Car

CARRYALL 2

UTILITY VEHICLE



CARRYALL

2

IQ Plus System™ (Electric Models only): Featured on the Carryall 2 and 6, this Club Car exclusive electrical system is the most advanced DC drive train technology in its class. IQ Plus improves energy management and increases the usable range of



the vehicle, while enhancing the service capabilities of the 48-volt platform. Along with its best-in-class load-carrying capabilities, this leading-edge system allows the user to program speeds, motor braking and acceleration.



Features

Club Car's exclusive IQ Plus System electric or 11.5 hp gas engine



15.3 ft³ (0.4 m³) cargo box carries 800 lb (363.2 kg)



Rugged, rustproof aluminum frame, chassis and cargo box



Self-adjusting rack & pinion steering




ArmorFlex® front body for fade-resistant color



Standard Color: Dark Gray



Optional Colors: Beige Gray, Green, White, Classic Blue, Red, Black and Burgundy



Trailer hitch



6-ply, premium tread front/extra-traction tread rear tires



Smooth, independent front and semi-independent rear suspension

Additional Features

- **Maximum speed of 17 mph (27.3 kph)** (Electric vehicles only)
- **1,200 lb (544.8 kg) total vehicle capacity**
- **Maximum hp @ 3,600 rpm exceeds SAE J1940 Performance Standards**
- **Side fuel fill**
- **Reconfigured dash**
- **48-volt IQ Plus electric motor or 351 cc, 11.5 hp gas, pedal-start engine**
- **Redesigned hip restraint for maximum styling and comfort**

Specifications

	<i>Carryall 2 Electric</i> <small>with exclusive IQ Plus System</small>	<i>Carryall 2 Gasoline</i>	
POWER SUPPLY	Engine	N/A	Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
	Drive Motor	48-volt Shunt/Sepex	N/A
	Horsepower	3.7 @ 3400 rpm (continuous) 21.0 @ 2000 rpm (peak)	11.5**
	Governor	N/A	Automatic ground speed sensing, internally geared-in unitized transaxle
	Governed RPM	N/A	3170±30
	Drive Unit	12.3:1 direct-drive axle, double-reduction helical gear	Electronic w/electronic RPM limiter Unitized transaxle, helical gears
	Electrical System	48-volt	12-volt, 500 cca 105 min. reserve
	Batteries	Eight 6-volt, Standard: T105 = 115 min @ 75 amps; Heavy Duty: T145 = 145 min @ 75 amps	N/A
	Charger	Automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed; International CE marked available	N/A
Controller	500 amp Solid State	N/A	
STEERING/ SUSPENSION	Steering	Self-adjusting rack & pinion	Self-adjusting rack & pinion
	Front Suspension	Independent leaf spring w/dual hydraulic shocks	Independent leaf spring w/dual hydraulic shocks
	Rear Suspension	Leaf springs w/dual hydraulic shocks	Leaf springs w/dual hydraulic shocks
	Brakes	Four-wheel mechanical drum	Four-wheel mechanical drum
	Park Brake	Foot-operated, multi-lock	Foot-operated, multi-lock
	Stabilizer Bar	No	Yes
FRAME/CHASSIS	Frame/Chassis	Aluminum I-Beam	Aluminum I-Beam
	Front Body	ArmorFlex®	ArmorFlex®
	Rear Body	All aluminum	All aluminum
	Body Finish	Matching paint over molded-in color	Matching paint over molded-in color
	Light Package	Optional	Optional
	Trailer Hitch	Standard	Standard
	Front Tires	18 x 8.50-8, 6-ply rated, Premium tread	18 x 8.50-8, 6-ply rated, Premium tread
	Rear Tires	18 x 8.50-8, 6-ply rated, Extra-Traction tread	18 x 8.50-8, 6-ply rated, Extra-Traction tread
	Instrumentation	Battery warning light	Electronic fuel gauge/hour meter, low-oil warning light
DIMENSIONS	Cargo Box Size	48.8" x 49.8" x 10.9" (15.3 ft ³) 123.8 cm x 126.4 cm x 27.6 cm	48.8" x 49.8" x 10.9" (15.3 ft ³) 123.8 cm x 126.4 cm x 27.6 cm
	Flat Bed Size	46.9" x 48.3" (119.1 cm x 122.7 cm)	46.9" x 48.3" (119.1 cm x 122.7 cm)
	Bed Height	27.5" (69.9 cm)	27.5" (69.9 cm)
	Bed Capacity	800 lb. (363.2 kg)	800 lb. (363.2 kg)
	Total Vehicle Capacity	1200 lb. (544.8 kg)	1200 lb. (544.8 kg)
	Overall Length	111" (281.9 cm)	111" (281.9 cm)
	Overall Width	50.0" (127.0 cm)	50.0" (127.0 cm)
	Overall Height	48.0" (121.9 cm)	48.0" (121.9 cm)
	Wheelbase	77.5" (196.9 cm)	77.5" (196.9 cm)
	Ground Clearance Under Differential	4.5" (11.4 cm)	4.5" (11.4 cm)
	Fuel Tank Capacity	N/A	7.0 gallons (26.5 Liters)
	Tread	34.5"/38.5" (87.6 cm/97.8 cm)	34.5"/38.5" (87.6 cm/97.8 cm)
	Dry Weight Less Batteries	612 lb. (277.8 kg)	724 lb. (328.7 kg)
	Speed Range	5-17 mph (8-27.3 kph)	14-16 mph (22.5-25.7 kph)
	Outside Clearance Circle	20.7 ft. (6.3 m) dia.	20.7 ft. (6.3 m) dia.
Turning Radius	10.0 ft. (3.0 m)	10.0 ft. (3.0 m)	
Intersecting Aisle Radius	77.0" (195.6 cm)	77.0" (195.6 cm)	
Vehicle Warranty	2-year limited*	2-year limited	

*4-year, limited battery warranty for electric vehicles
**Exceeds SAE J1940 Performance Standards